




1202



Great Productivity

- 
NDC (No Dirt in Curve)
Automatic brush movement
whilst curving
- 
Huge hopper capacity
- 
Large sweeping path

PATENTED

High Performance

- 
SLS (Self Levelling System) automatic main brush pressure control
- 
Dust micro filtration
- 
Dust flap for large debris collection
- 
Pre-programmed working settings
- 
Adjustable side brush rpm

PATENTED

Ergonomics, User Friendly

- 
Easy to use control panel
- 
Great visibility whilst working
- 
Effective discharge system thanks to separate controls for hopper raise and tilting
- 
Automatic stop (by comand release) in working mode



PATENTED

SLS (Self Levelling System) automatic brush pressure control

System that adapts immediately the brush thanks to a special shock absorber. The actuator moves only in case brush adapting requirements are higher. The system allows the brush:

- to immediately and constantly follow all types of surfaces
- to self adjust brush pressure until the brush is completely worn out.

No need to check brush wear as brush replacement is indicated automatically on control panel display.

Technical data		1202 E	1202 DP
Max working width	mm	1200	1200
Main brush width	mm	700	700
Productivity (at max speed)	m ² /h	8400	8400
Dirt container volume	l	115	115
Max dumping height	mm	1000	1000
Power supply		Battery 24V	Dual Power (Petrol) Honda 5,5 HP - 24V
Filter surface	m ²	4	4
Electric filter shaker		Automatic	Automatic
Max speed	Km/h	7	7
Weight (net)	Kg	244	284
Dimensions (LxWxH)	mm	1550x926x1175	1550x926x1175



Low Maintenance Costs



Main brush replacement without tools



Dust filter replacement without tools



Self cleaning filter system



Automatic main brush lift in reverse

Robust Construction



Heavy duty chassis in fully coated steel



Maximum protection against impact



Panel control switches protected against water and humidity



PATENTED



NDC (No Dirt in Curve) Automatic brush movement whilst turning

- Whilst curving the side brush moves inwards automatically.
- The system avoids uncollected debris whilst turning.




Pre-programmed working settings

3 independent programs allow best settings for all types of applications. Filter shaker can be operated at any time. Each program can be fully personalized.



Effective discharge system thanks to separate controls for hopper raise and tilting

Hand assisted raising system by the means of two gas pistons. Maximum dump height of 1 meter. Hand assisted hopper tilting system.



IPC